

Moneysworth & Best 120 Midair Court Brampton, ON, L6T 5V1 Canada 905-790-0650

29648_Dark Bone BCS 127g/4.5oz PRODUCT: **CODE: 29648**

SECTION 01: IDENTIFICATION

29648 Dark Bone BCS 127g/4.5oz Product Identity.....

Product Item Numbers..... 29648

Moneysworth & Best 120 Midair Court Supplier..... Brampton, ON

Canada L6T-5V1

905-790-0650 In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800) 24 hour emergency telephone number.....

424-9300.

Recommended Use..... Leather Coloring.

SECTION 02: HAZARD IDENTIFICATION



Hazard Classification:

Physical Hazards.....

Gases Under Pressure - Liquefied Gas. Flammable Aerosols - Category 2. Eye Damage/Irritation - Category 2A. Crcinogenicity Category 1A. Germ Cell Mutagenicity -Health Hazards..... Category 1B. Reproductive Toxicity - Category 2. Specific Target Organ Toxicity, Repeated Exposure - Category 1. Specific Target Organ Toxicity, Single Exposure Category 3

narcotic effects.

Environmental Hazards..... Hazardous to the aquatic environment, acute hazard Category 3. Hazardous to the aquatic

environment, long-term hazard Category 3. Label Elements:

DANGER.

Signal Word.....

H223:Flammable aerosol. H372:Causes damage to organs through prolonged or Hazard Statement.....

repeated exposure. H335:May cause respiratory irritation. H350:May cause cancer. H340:May cause genetic defects. H280:Contains gas under pressure; may explode if heated (L). H229:Pressurized container: may burst if heated (1). H319:Causes serious eye irritàtion. H336:May cause drowsiness or dizziness. H361:Suspected of damaging

fertility or the unborn child. Toxic to aquatic life with long lasting effects.

Precautionary Statements:

Prevention.....

P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251:Do not pierce or burn, even after use. P260:Do not breathe dust/ fume/gas/ mist/ vapours/spray. P270:Do not eat, drink, or smoke when using this product. P211:Do not spray on an open flame or other ignition source. P271:Use only outdoors or in a well-ventilated area. P203: Obtain, read and follow all safety instructions before use. P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.

P264:Wash hand thoroughly after handling. P318: If exposed or concerned, get medical

advice.

P304+P340:IF INHALED: Remove person to fresh air and keep comfortable for breathing. Response..... P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P319:Get medical help if you

feel unwell. P337+P317:If eye irritation persists: Get medical help. P403:Store in a well ventilated place . P233:Keep container tightly closed. P405: Store Storage.....

locked up. P410+P412:Protect from sunlight. Do not expose to temperatures exceeding

50°C /122°F.

P501:Dispose of contents/container in accordance with local, regional, national, and/or Disposal.....

international regulations.

Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS			
CHEMICAL NAME AND SYNONYMS	CAS#	WT. %	
Acetone	67-64-1	15-40	
n-Butane	106-97-8	10-30	
Ethyl Acetate	141-78-6	7-13	

PRODUCT: 29648_Dark Bone BCS 127g/4.5oz

Xylene

Propylene Glycol Me Ethyl Benzene Methyl Ethyl Ketone Titanium Dioxide

Other Ingredient(s)

and delayed

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS			
	1330-20-7	5-10	
ethyl Ether Acetate	108-65-6	1-5	
	1000-41-4	1-5	
	78-93-3	1-5	

13463-67-7

SECTION 04: FIRST-AID MEASURES

If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain Inhalation..... immediate medical assistance. Check for and remove contact lenses. Immediately flush eyes with water for a minimum of Eye Contact.....

15 minutes keeping eyelids open. Consult a doctor if any irritation occurs. Get medical attention if irritation persists.

Remove contaminated clothing. Launder clothing before reuse. Wash thoroughly with soap Skin Contact..... and lukewarm water. If irritation occurs consult with your doctor.

Not likely to be ingested. If occurs, do not give anything by mouth to an unconscious Ingestion..... person. Do not induce vomiting, get medical attention. Obtain medical advice. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain. Most important symptoms/effects, acute ..

Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

1-5

10-30

CODE: 29648

SECTION 05: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media..... Dry chemical powder. Carbon dioxide. Foam, water spray or fog.

Special Protective Equipment and Firefighters must use standard protective equipment including flame retardant coat, helmet Precautions for Firefighters with water to prevent vapor pressure build up. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from immediate hazard area if it is safe to do.

General Fire Hazards..... Extremely flammable aerosol.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator Personal Precautions, Protective **Equipment and Emergency Procedures** when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08)

Methods and Materials for Containment .. and Cleaning Up

Indication of immediate medical attention

and special treatment needed

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent

Environmental Precautions..... environmental contamination.

SECTION 07: HANDLING AND STORAGE

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Precautions for Safe Handling..... Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Wear appropriate protective equipment.

Conditions for Safe Storage including any Incompatibilities

Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

CODE: 29648

PRODUCT: 29648_Dark Bone BCS 127g/4.5oz

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	CGIH TLV STEL	OSI PEL	HA PEL STEL	NIOSH REL
Acetone	250 ppm	500 ppm	1,000 ppm (2,400 mg/m3)	Not available	Not available
n-Butane	800 ppm	Not available	Not available	Not available	Not available
Ethyl Acetate	400 ppm	Not available	400 ppm (1,400 mg/m3)	Not available	Not available
Xylene	50 ppm	150 ppm	100 ppm (435 mg/m3)	Not established	Not established
Propylene Glycol Methyl Ether Acetate	Not established	Not established	Not established	Not established	Not established
Ethyl Benzene	100 ppm	125 ppm	100 ppm	No data	100 ppm
Methyl Ethyl Ketone	200 ppm	300 ppm	200 ppm (590 mg/m3)	300 ppm (885 mg/m3)	200 ppm (590 mg/m3)
Titanium Dioxide	10 mg/m3	Not established	15 mg/m3	Not established	Not established
Appropriate Engineering	•	Local exhaust ventilation Value if unprotected per use.			
Eye/Face Protection			skin. Wear		
, 0	such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.			ing, and/or smoking.	

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid. Aerosol. Not available. Not available187.6 °C (-305.68 °F)42.1°C (-43.78°F). Not available. Not applicable104.4 °C (-156.0 °F). 26.46 kJ/g estimated. 1.9% estimated. Not available. Not available. 287.78 °C (550 °F) estimated.
Partition Coefficient (n-Octanol/Water) Percent Volatile	Not available. 89.98.
Relative DensitySolubility in water	not available. Not available .
Specific Gravity Upper Explosive Limit (%, vol)	0.75. 12.8% estimated.
Vapour Density (Air=1)	Not available.
Vapour Pressure (psig) VOC Content	2271.31 hPa estimated. 5.11 lbs/gal Regulatory 612.5 g/l Regulatory 3.39 lbs/gal Material 405.72 g/l Material.
Flammability Class Oxidizing Properties	Flammable IA estimated . Not oxidizing

SECTION 10: STABILITY AND REACTIVITY

	Product not reactive under normal conditions of use. Stable at normal temperatures and pressures.
Possibility of Hazardous Reactions Conditions to Avoid Incompatible Materials	Will not occur. Avoid sources of heat and flame, and electrostatic charge.



PRODUCT: 29648_Dark Bone BCS 127g/4.5oz

SECTION 11.	TOYICOL	OCICAL	INFORMATION
SECTION 11:	TUXICUL	UGILAL	INFURINATION

INGREDIENTS	LC50	LD50
Acetone	71 mg/L (Rat - 4 hrs)	5,800 mg/kg (Oral - Rat); >15,800 mg/kg (Dermal - Rabbit)
n-Butane	658 mg/L (Rat - 4 hrs)	Not available
Ethyl Acetate	28.8-57.7 mg/L (Rat - 4hrs)	10,200 mg/kg (Oral - Rat); >18,000 mg/kg (Dermal - Rabbit)
Xylene	27.6 mg/L (Rat - 4 hrs)	3,253 mg/kg (Oral - Rat); 12,180 mg/kg (Dermal - Rabbit)
Propylene Glycol Methyl Ether Acetate	3,350mg/m3 (8hrs)	8,532mg/kg (Oral - Rat); 5,000mg/kg (Dermal - Rabbit)
Ethyl Benzene	No data	3,500 mg/Kg (oral-rat)
Methyl Ethyl Ketone	>5,000 ppm (Rat - 6hrs)	3,400 mg/kg (Oral - Rat); >8,000 mg/kg (Dermal - Rabbit)
Titanium Dioxide	Not available	>10,000 mg/kg (Oral - Rat); >10,000 mg/kg (Dermal - Rabbit)

Information on Likely Routes of Exposure:

Routes of entry - Inhalation.....

Yes. May cause irritation of respiratory tract.

Routes of entry - Skin & Eye..... Yes. Direct contact with eyes may cause temporary irritation. May cause irritation.

Harmful if swallowed.

Symptoms Related to the Physical, Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred Chemical and Toxicological Characteristics vision. Defatting of the skin. Symptoms of overexposure may be headache, dizziness,

CODE: 29648

tiredness, nausea and vomiting. Harmful if swallowed. Narcotic effects. Acute Toxicity.....

Skin Corrosion/Irritation..... Causes skin irritation.

Serious Eye Damage/Eye Irritation..... Causes serious eye irritation. Respiratory or Skin Sensitization......Germ Cell Mutagenicity..... Not known to be a sensitizer. May cause genetic defects.

Carcinogenicity..... Suspected to have carcinogenic effect. Reproductive Toxicity..... Suspected to have reproductive effect.

STOT - Single Exposure..... Specific target organ toxicity single exposure Category 3. May cause drowsiness and

dizziness.

STOT - Repeated Exposure..... May cause damage to the organs through prolonged or repeated exposure.

Aspiration Hazard..... No data available.

Prolonged inhalation may be harmful. Chronic Effects.....

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity..... Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. This material and its container must be disposed of as hazardous waste.

Avoid release to the environment.

The product itself has not been tested.

Persistence and degradability Bioaccumulation Potential..... The product itself has not been tested.

Mobility in Soil..... The product itself has not been tested.

Other Adverse Effects..... None Known.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... UN number UN1950 UN proper shipping name Aerosols, Flammable Class 2.1 Transport hazard class(es) Subsidiary risk - Packing group Not applicable. Environmental hazards

Not available. Special precautions for user Read safety instructions, SDS and emergency

procedures before handling.

UN number UN1950 UN proper shipping name Aerosols, Flammable Class 2.1 Transport IATA (International- Air).....

hazard class(es) Subsidiary risk - Label(s) 2.1 Packing group Not applicable.

Environmental hazards No. Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Passenger and cargo Allowed. aircraft Other

information Cargo aircraft only Allowed. .



PRODUCT: 29648_Dark Bone BCS 127g/4.5oz

SECTION 14: TRANSPORT INFORMATION

IMDG (International- Marine).....

UN number UN1950 UN proper shipping name Aerosols, Flammable, MARINE POLLUTANT Class 2.1 Transport hazard class(es) Subsidiary risk - Label(s) 2.1 Packing group Not applicable. Marine pollutant Yes Environmental hazards EmS Not available. Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code.

CODE: 29648

SECTION 15: REGULATORY INFORMATION

Canada Regulations:.....

Precursor Control Regulations ACETONE (CAS 67-64-1) Class B METHYL ETHYL KETONE (CAS 78-93-3) Class B. Controlled Drugs and Substances Act: Not regulated. Export Control List (CEPA 1999, Schedule 3): Not listed. Greenhouse Gases: Not listed. All components are either listed or exempt from the TSCA.

TSCA Inventory Status..... California Proposition 65.....

This product contains a chemical known to the State of California to cause cancer. ETHYLBENZENE (CAS 100-41-4), TITANIUM DIOXIDE (CAS 13463-67-7).

SECTION 16: OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. THIS SDS IS VALID FOR THREE YEARS. The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical

Abbreviations.....

Abstract Service: NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous

Materials Information System STOT: Specific Target Organ Toxicity.

Prepared by Latest Revision Regulatory Affairs 2022-02-20